

Zoe Competition



COLORED AND VERSATILE

Totally matching every type of decorative solution thanks to the possible customizations



SHOT TIMER

To accurately and reliably time coffee extraction



LED LIGHTING OF THE WORKING AREA

Allows to effectively work in any light condition



EASY SERVICE

Fast access to the internal parts for quick and easy technical service



LOW SERVICE COST

Designed to decrease the maintenance and inspection costs



Characteristics



ELECTRONIC AUTO-LEVEL
Through an electronic level probe the boiler is automatically filled and maintained to the right filling level.



ACTIVATED ELECTRONIC PRE-INFUSION
Management of the delayed activation of water solenoid in the first phase of brewing.



DOUBLE READING GAUGE
Allows to control at the same time the boiler pressure and the distribution pressure.



EASY SERVICE
Fast access to the internal parts for quick and easy technical service.



AUTOMATIC CLEANING CYCLE
Process for coffee groups cleaning.



LED LIGHTING OF THE WORK AREA
Allows efficient working in any condition of environmental lighting.



SHOT TIMER
To accurately and reliably time coffee extraction.

Other



AUTOSTEAMER
Steam wand characterized by an electronic system that allows to mount and/or heat milk at the set temperature.



CUP WARMER
Dedicated resistor to keep all the cups at the optimal temperature.



EXTERNAL VOLUMETRIC PUMP



NAKED FILTER HOLDERS



ENHANCED RESISTANCE

| Technical data | | 1 group | 2 group | 3 group |
|------------------------------------------------|---------|-------------------------|------------|-----------|
| voltage | V | 220-240 1N / 380-415 3N | | |
| max input boiler/steam boiler's resistor power | kW | 2.35 / 1.95 | 3.35 / 2.7 | 5.8 / 5.1 |
| | | 4.3 / 4.0 | | |
| | | 4.8 / 4.5 | | |
| steam boiler capacity | lt | 5 | 9 | 12.5 |
| pump power | kW | 0.15 | 0.15 | 0.15 |
| net weight | lb / kg | 93 / 42 | 121 / 55 | 152 / 69 |
| gross weight (with shipping crate) | lb / kg | 104 / 47 | 130 / 59 | 161 / 73 |